

# Oferta węży hydraulicznych - P.P.H.U. POKORA

P.P.H.U. POKORA Wiesław  
ul. K. Idzikowskiej 11, 92-624 Łódź  
tel./fax (42) 648 88 01, kom. 501 587 853



## WĄŻ 1SN

Wąż jednoplotowy

### DANE TECHNICZNE

Zakres temperatur :  
-40°C to +100°C (+120°C max.)  
Wykonanie :  
Olejoodporna syntetyczna guma

TYP	DN [mm]	DN [cale]	ciś. rob. [bar]	Waga kg/m
1 SN	06	1/4"	225	0,21
1 SN	08	5/16"	215	0,24
1 SN	10	3/8"	180	0,33
1 SN	13	1/2"	160	0,41
1 SN	16	5/8"	130	0,45
1 SN	20	3/4"	105	0,58
1 SN	25	1"	88	0,88
1 SN	32	1 1/4"	63	1,23
1 SN	40	1 1/2"	50	1,51
1 SN	50	2"	40	1,97



## WĄŻ 2SN

Wąż dwuplotowy

### DANE TECHNICZNE

Zakres temperatur :  
-40°C to +100°C (+120°C max.)  
Wykonanie :  
Olejoodporna syntetyczna guma

TYP	DN [mm]	DN [cale]	ciś. rob. [bar]	Waga kg/m
2 SN	06	1/4"	400	0,33
2 SN	08	5/16"	350	0,39
2 SN	10	3/8"	330	0,5
2 SN	13	1/2"	275	0,59
2 SN	16	5/8"	250	0,71
2 SN	20	3/4"	215	0,86
2 SN	25	1"	165	1,28
2 SN	32	1 1/4"	125	2,02
2 SN	40	1 1/2"	90	2,23
2 SN	50	2"	80	2,85



## WĄŻ 4SP

Wąż czterosplotowy do skórowania

### DANE TECHNICZNE

Zakres temperatur :  
-40°C to +100°C (+120°C max.)  
Wykonanie :  
Olejoodporna syntetyczna guma

TYP	DN [mm]	DN [cale]	ciś. rob. [bar]	Waga kg/m
4 SP	06	1/4"	485	0,65
4 SP	10	3/8"	445	0,78
4 SP	13	1/2"	415	0,93
4 SP	16	5/8"	350	1,17
4 SP	20	3/4"	350	1,48
4 SP	25	1"	280	2,02
4 SP	32	1 1/4"	210	3,05
4 SP	40	1 1/2"	185	3,52
5 SP	50	2"	165	5,2



## WĄŻ 4SH

Wąż czterosplotowy do skórowania

### DANE TECHNICZNE

Zakres temperatur :  
-40°C to +100°C (+120°C max.)  
Wykonanie :  
Olejoodporna syntetyczna guma

TYP	DN [mm]	DN [cale]	ciś. rob. [bar]	Waga kg/m
4 SH	06	3/4"	420	1,53
4 SH	08	1"	380	2,06
4 SH	10	1 1/4"	345	2,46
4 SH	13	1 1/2"	290	3,35
4 SH	16	2"	250	4,55